TutorCat

USER GUIDE

Guide for Admins

Run TutorCat day to day: accounts, invites, plans, AI spend and settings.

Contents

1. The operations console at a glance 3
2. Signing in and your 30-minute session 8
3. Overview and launch readiness 12
4. Engagement 16
5. Users 19
6. Invites and the welcome email 25
7. Feedback inbox 30
8. Packages and pricing 32
9. Payments 37
10. AI and usage 40
11. Models 47
12. Lesson Library 61
13. Costs 65
14. Settings and flags 70
15. The audit log 81
16. The privacy boundary 84
17. Daily beta operations 86
18. Admin FAQ 90

ADMINS

The operations console at a glance

What the admin console is for, how it is laid out, and the two rules that shape every screen.

The operations console lives at **tutorcat.ai/admin**. It is for TutorCat staff running the invite-only beta. You use it to issue invite codes, watch the platform's health and spend, read feedback, manage accounts, and change platform settings.

It is a separate place from the product. It has its own sign-in, and a normal parent or student account can never open it.

Two rules that shape every screen


1. **Every change needs a written reason.** Suspending an account, revoking an invite, changing a setting, a price or the AI budget: each one asks why. The reason is written to the **Audit log** before the change happens. If the audit entry cannot be written, the change does not happen.
2. **Admins never see what children write.** The console shows counts and account details only. There is no screen that opens a student's messages, notes, photos or transcripts. See **The privacy boundary** in this guide.

How the console is laid out

On a computer, the left sidebar holds every section. From top to bottom:

Sidebar item	What you do there
Overview	Launch readiness, headline figures and seven-day charts. Start here every day.
Engagement	Sessions, active students and the sign-up funnel, as totals only.
Users	Find an account, see its details, suspend or erase it.
Invites	Create and revoke family invite codes.
Feedback	Read notes families sent from inside the app.
Packages	The plan tiers and the packages that can be bought.
Payments	The payments ledger. Payments are off during the beta.
Pricing	What each plan costs, and the price history.
AI & Usage	Today's AI spend against the daily budget, token use, the speech model and model prices.
Models	Which AI model does each job, with backups, the OpenRouter key, safety tests and failovers.
Costs	What AI costs by day, job, model and account, with CSV export.
Settings	Registration, provider keys, email, budgets and the beta switches.
Audit log	Every admin change, with who made it and why.


Below the list are **Sign out**, the **Session** timer and the email you signed in with.



The Overview page with the sidebar, session timer and launch readiness card

1. **Launch readiness**
2. **How many rows are ready**
3. **Headline figures**
4. **The last seven days**
5. **Every console section**
6. **Session time left**
7. **Sign out**

On a tablet the sidebar shrinks to a row of icons. On a phone, the sections move into a menu: tap **Open menu** at the top right.



The console on a phone, with the section menu open

1. **Tap a section**
2. **Sign out here**

How reasons work

Most changes open a confirm box with a **Reason** field.

- The reason must be between 20 and 500 characters. A counter under the field shows how many you have typed.
- The confirm button stays greyed out until the reason is long enough.
- Write what happened and why, for example "Parent asked by email to pause the account while they review screen time."
- Do not paste the requester's email or other personal details into the reason. The field says so too.

Some forms (Invites, Settings rows, Packages and Pricing) have the **Reason** field on the page instead of in a box. It is still required and still goes to the audit log.

GOOD TO KNOW

Every change takes effect without a restart. AI, speech and email settings apply within a minute.

ADMINS

Signing in and your 30-minute session

Sign in with your email, password and a six-digit authenticator code. Sessions last 30 minutes.

Admin sign-in always needs three things: your email, your password, and the six-digit code from your authenticator app. There is no password-only mode and no reset by email.

Before your first sign-in: set up your authenticator

Admin accounts cannot be created from the console or by signing up. Engineering creates your account for you.


1. When engineering creates your account, you type your own password at their prompt. It must be at least 12 characters. Use it only for TutorCat, and do not tell it to anyone.
2. Engineering gives you a one-time setup link that starts with `otpauth://`. It is shown **once only**.
3. Load it straight away into an authenticator app on your own phone. Any standard authenticator app works: add an account and paste the link or the key it contains.
4. Check that the app now shows a TutorCat code that changes every 30 seconds.
5. Delete any copy of the setup link from chat or email. Anyone holding it can make your codes.

SAFETY

One admin account per person. Never share an account, a password or an authenticator.

Sign in

1. Go to **tutorcat.ai/admin**. You see **Admin sign-in**.



The admin sign-in screen with email, password and six code boxes


1. **Your admin email**
2. **Your password**
3. **Six-digit authenticator code**
4. **Sign in**

2. Type your **Email** and **Password**.
3. Open your authenticator app and type the current code into the six boxes under **Authenticator code**. You can paste it; spaces are removed for you.
4. Select **Sign in**.

The console opens on **Overview**. If you opened a deeper link (for example `/admin/invites`) before signing in, you land there instead.

If sign-in is refused

You see **Sign-in refused. Check your email, password, and authenticator code, then try again.** The code boxes clear.



The sign-in screen after a refused attempt

1 **Same message for any mistake** 2 **Wait for a fresh code**

The message is the same whatever was wrong, on purpose: it never tells anyone which part was right.

- Wait for the next code before trying again. **Each code works only once**, even within its 30 seconds.
- The code from the previous 30 seconds is still accepted, so a slow phone clock is fine. Older codes are not.
- If your phone's clock is far out, set it to automatic time.

If you see a message that **Sign-in is unavailable** because the server cannot open authenticator secrets, nothing you type will work. Tell engineering; it is a server setting, not your password.

Your 30-minute session

- A session lasts **30 minutes** from sign-in. It is not extended by activity.
- The **Session** timer in the sidebar counts down (on a phone it sits in the top bar). It turns to a warning colour in the last five minutes.
- For the last five minutes, a banner at the bottom of every page says **Session expires in 4:59.** and **Sign in again after it ends to keep working.**
- When the timer reaches zero you return to the sign-in screen with **Your admin session ended. Sign in again to continue.**

- There is no "extend" button. Sign in again with a fresh code.

> **TIP**
> Finish a change before the last minute. A reason you were typing is lost when the session ends.

The session lives only in that browser tab. Closing the tab ends it, which keeps a shared computer safe.

Sign out

Select **Sign out** at the bottom of the sidebar (on a phone, open the menu first). This ends the session in that tab.

Lost or new phone


You cannot move your authenticator yourself. Ask engineering to re-enrol you. You get a new one-time setup link, and the old authenticator stops working at once.

ADMINS

Overview and launch readiness

The landing page. Read the launch readiness card, the six headline figures and the seven-day charts.

Overview is the first page after sign-in. Everything on it is a total or a count. Nothing here can identify a student or a parent.



Overview: launch readiness, headline figures and seven-day charts

1. Launch readiness
2. How many rows are ready
3. Headline figures
4. The last seven days
5. Every console section
6. Session time left
7. Sign out


Launch readiness

The **Launch readiness** card has nine rows. Each row has a coloured dot: green for ready, red for not ready, grey for unknown. The top right says how many are ready, for example **8 of 9 ready**.

Row	What it means	Green when	How to make it green
Tutor	Whether real tutor replies are being served.	**Live**	Save a valid provider key in **Settings → AI keys → Anthropic API key**. It shows **Stub (canned replies)** until then. If a saved key still shows Stub after a minute, tell engineering.
Email	Whether emails (consent links, safety alerts, budget alerts) really go out.	**Sending**	Fill in every field of the **SMTP** group in Settings. **Logging only** means emails are written to a log and nobody receives them.
Speech	Whether voice input can be transcribed.	**Configured**	Save the **Speech-to-text API key** in **Settings → AI keys**. **Missing** means voice input will not work.
Payments	Whether checkout can take money.	**Live**	**Off** is expected and correct for the whole beta. Leave it. See **Payments** in this guide.
Registration	Who can sign up: **Invite only** or **Open**.	Always green	Informational. During the beta it must say **Invite only**.
Safety events (24h)	How many safety events happened in the last 24 hours, across all students.	Always green	Informational. A count only; see the daily checklist for what to do with it.
AI spend today	Today's AI spend against the daily budget, for example **$3.18 of $25.00**.	Under budget	Red means the budget is used up and the tutor is paused. See **AI and usage** in this guide. Grey **Spend unknown** means the spend

Row	What it means	Green when	How to make it green
			could not be read just now; the tutor keeps working.
Version	The build that is running. **dev** means a development build.	Always green	Informational. Quote it when you report a bug.
Dev flags	Development-only switches in the server's environment.	**None on**	They cannot be changed from the console. Hover to see their names, then ask engineering to remove them. Any dev flag blocks going public.

During a healthy beta you should see **8 of 9 ready**: everything green except **Payments: Off**.



A launch readiness card with several rows not ready

1. Save the provider key
2. Complete SMTP settings
3. Save the speech key
4. Engineering removes these
5. Grey means unknown

GOOD TO KNOW

Before you go public, Tutor, Email and Speech must be green and Dev flags must say None on. Payments stays Off for a free launch. The full list of gates is in the go-public checklist.

The headline figures

Card	What it shows
Accounts	All accounts, with students and parents underneath.
Students	Student accounts, and how many finished onboarding.
Parents	Parent accounts.
Consent rate	Granted consents as a share of all consents asked for, with granted and pending counts.
Sessions, 7d	Tutoring sessions in the last seven days, and the median session length.
Tokens, 30d	AI tokens used in the last 30 days, with the cost underneath. **Not fully priced** means some tokens came from a model with no price set (see Model prices).

A card that says **No data yet** has nothing to count. **Not available yet** means the server does not offer that figure yet.

The charts

Three bar charts cover the last seven days: **Sessions per day**, **Tokens per day** and **Signups per day**. A day with nothing on it shows as a gap, not a made-up value.


Deeper cuts live under **Engagement**, **AI & Usage** and **Payments**.

ADMINS

Engagement

Sessions, active students, the sign-up funnel and how often students come back, as totals only.

Engagement answers "are families using it?" Every figure is a count or a median. No figure on this page can identify a student or a parent.



The Engagement page with the window switch, figures, daily chart, funnel and active days

1. Pick 7, 30 or 90 days
2. Totals for the window
3. Active students per day
4. Sign-up to first homework
5. How often students return

Choose a window

Use the **7d**, **30d** and **90d** buttons at the top right. Every figure and chart on the page follows the window, except the funnel, which always counts everything so far.

What each part shows

Part	What it shows
Sessions (for example **Sessions 30d**)	Tutoring sessions in the window.
Active students	Students active in the last seven days out of all student accounts, with the weekly share as a percentage.
Median length	The median session length. **Not enough data** when there are too few sessions to say.
Daily active students	A bar for each day in the window, with the median per day in the corner. Hover or focus a bar for its exact count.
Funnel	**Registered accounts**, **Student profiles**, **Onboarded**, **Consent requested**, **Consent granted**, **First homework session**. Each row shows the count and its share of registered accounts.
Active days per student, this window	How many students were active on how many days. It shows whether students come back.

Below the cards:

- A line with the median session length.
- A note from the server when the window holds too little data to support a claim. It is shown exactly as sent; do not read more into small numbers than it allows.
- **Data table**: open it to see sessions and active students for each day as plain numbers.

Using it in the beta

- **Families who signed up but never started.** Compare **Consent granted** with **First homework session** in the funnel. A gap means families got stuck after consent. Message them (see the daily checklist), never look for their content.
- **Week-3 retention.** The runbook's exit target is at least 70% of families active in week 3. Use the 7d window and the **Active students** card each week and write the figure in the weekly metrics row.
- **Stuck consent.** A large gap between **Consent requested** and **Consent granted** can mean consent emails are not arriving. Check that **Email** says **Sending** on Overview.




ADMINS

Users

Find an account, read its details, and suspend, unsuspend or erase it with a written reason.

Users lists accounts: email, role, plan, profile count, status and created date. That is all an admin can see about an account. Nothing a student wrote is reachable from here.

Find an account



The Users list with search, role filter and status filter

1. Search email or id
2. Filter by role
3. Active or suspended
4. Open an account
5. A suspended account

1. Open **Users** in the sidebar.


2. Type in **Search by email**. You can also type the start of an account id, for example the eight characters shown under an email or next to a feedback note.
3. Narrow by role with **All**, **Students**, **Parents** or **Admins**.
4. Narrow by **Status: Any**, **Active** or **Suspended**.
5. Select a row (or the email) to open the account.

What the columns mean:

Column	Meaning
Account	The email, and the first eight characters of the account id.
Role	**Student**, **Parent** or **Admin**.
Plan	The paid subscription, if any. During the beta it shows — for everyone: families get Family features through the beta switch, not a subscription.
Profiles	Student profiles on the account. A student account has 1; a parent account has 0.
Status	**active** or **suspended**. Hover a suspended pill for the date.
Created	When the account was created.

The list loads up to 200 accounts, newest first. When it says **Showing the first 200 matches**, use the filters to narrow it. The list shows eight rows a page; use the page numbers under the table.

Read an account



An account's detail page with the Actions card

1. **Email, role and id**
2. **Account metadata only**
3. **No access to content**
4. **Suspend with a reason**
5. **Erase on request only**

The detail page shows the email, role, full account id, **Created**, **Plan**, **Student profiles** and, when suspended, the **Suspended** date.


Under the details: **Session content, portfolio and wellbeing data are not visible to administrators. Only counts and metadata.** This is by design and cannot be switched off.

Suspend an account

Suspending stops the account from signing in. Its data is kept, nothing is deleted, and you can undo it.

1. On the account's page, select **Suspend…** in the **Actions** card.
2. In **Reason (required, min 20 chars)**, write why. For example: "Parent asked by email to pause access while they review screen time."

3 Select **Suspend account**. Or **Cancel** to leave it as it is.



The suspend box with the reason field and the Suspend account button

1 **Why, in 20+ characters** 2 **Confirm the suspension** 3 **Or cancel**

4 The status changes to **suspended**. If the account is an administrator, their console sessions end at once.

To undo it, open the account and select **Unsuspend…**, give a reason, and select **Unsuspend account**. Sign-in works again and all the data is still there.

What the audit log records

Before the suspension takes effect, the **Audit log** gets a row with:


- **When**: the date and time.
- **Actor**: your account (the first eight characters of its id).
- **Action**: `suspend_user` (or `unsuspend_user`), with the account id as the target.
- **Reason**: exactly what you typed.
- **before / after**: `{"suspended": false}` and `{"suspended": true}` (the other way round for unsuspend).

If the audit row cannot be written, the suspension does not happen. If the suspension fails after the row is written, the row stays, so the attempt is still on record.

Erase an account

Erase is for a deletion request that reached you by email, for example a parent who cannot use the in-app delete. It is permanent and immediate. There is no undo.

1. On the account's page, select **Erase…**.
2. Read the box. It says exactly what will go:
   - For a **parent**: the account, its email everywhere it was copied, its consent grants (revoked) and its subscription (cancelled). **Their children's accounts are kept.** Erase each child separately if the request covers them.
   - For a **student**: the account and every homework conversation, photo, summary and event under it.
3. Write the reason, for example "Parent emailed beta@ on 24 Oct asking to delete their child's account."
4. In **Retype the account's email to confirm**, type the account's email. The button stays greyed out until it matches.
5. Select **Erase permanently**.



The erase box asking for a reason and the account's email retyped

1. **Why, in 20+ characters**
2. **Retype the account email**
3. **Permanent, no undo**

You return to the Users list. The audit row is `erase_user`.

SAFETY

Families can delete their own data from the parent area at any time. Use **Erase…** only when someone asks you to, and only for the account they asked about.

Administrator accounts cannot be erased from the console. **Reset password** and **Change role** do not exist in the console.


ADMINS

Invites and the welcome email

Create one invite code per family, send the welcome email, watch its uses, and revoke a lost code.

While sign-up is invite-only, nobody can create an account without a code. **Invites** is where you make those codes.

One code covers a family. The parent and each child use it once each when they sign up, so the default is **5** uses.



The Invites page: the code list on the left, the New invite form on the right

1. Family name
2. Parent plus children
3. Why it is issued
4. Create the code
5. Copy it for the email
6. Uses so far
7. Revoke a leaked code

Create a family code

1. Open **Invites** in the sidebar. (Or select **+ New invite** at the top; it jumps to the form.)
2. In **Label**, type the family name, for example **Rahman**. Use one code per family. If a second parent needs their own code, label it **Rahman 2**.
3. Leave **Max uses** at **5** unless the family is bigger. One parent plus four children is five.
4. In **Reason**, say why, for example "Beta wave 1, recruited through the school parents' group."
5. Select **Create invite**.
6. A line appears under the button: **Created K7QX-M2PD-9RTA. Send it to the family.** Select **Copy** next to it.

Codes look like `K7QX-M2PD-9RTA`. They never use 0, O, 1, I or L, so they survive being read aloud. Families can type them in lower case; they still match.

The audit log records `create_invite` with the label, the number of uses and your reason.

Send the welcome email

The console does not email families. You send the welcome email yourself.

1. Copy the code.
2. Send the welcome email from **beta@tutorcat.ai** using the parent welcome email template, filling in the family name and the invite code.
3. Send one email per family, never a bulk email, so no family sees another family's address.
4. Write the sent date in your private recruiting sheet.

Before you send, check that the code is the one labelled with this family.

The parent goes to tutorcat.ai, chooses **Sign up**, and types the code into **Invite code**. Each child who signs up types the same code.

Parents who arrive from a consent email

Some children sign up first and ask a parent for consent by email. In invite-only mode, that parent **also needs an invite code** to create their own parent account, even though they came from the consent link.

- Best: issue the code before the child signs up, and send it to the parent.
- If a child is already waiting: create a code labelled with the family name, for example **Rahman parent**, and send it to the parent straight away.

A child below their country's consent age cannot use the tutor until the parent approves.


Read the list

Column	Meaning
Code	The code itself.
Label	The family name you gave it.
Uses	For example **2 of 5**, with a bar.
Expires	**never** for normal codes.
Status	**active**: still usable. **used up**: every use taken. **expired**: revoked, or past its end date.

Copy puts the code on your clipboard. **Revoke** appears only on active codes.

Revoke a lost or leaked code

1. Find the code and select **Revoke**.
2. Write the reason, for example "Family says the email with the code was forwarded by mistake."
3. Select **Revoke**.



The Revoke invite box with the reason field

1 **Why it is revoked** 2 **Ends the code now**

4 The code stops working at once and shows **expired**. The row stays as a record.


Accounts already created with the code keep working. To replace the code, create a new one with the same label.

The audit log records `revoke_invite` with the code's state before and your reason.

> **GOOD TO KNOW**
> Codes only matter while **Who can sign up** is set to invite-only in Settings. When registration is open, anyone can sign up without a code.

On a phone

The Invites page works on a phone too, so you can copy a code while you message a family.



The Invites page on a phone


1. **Session time left**
2. **Jump to the form**
3. **Copy a code**

ADMINS

Feedback inbox

Read the notes families send from inside the app, newest first.

Feedback shows the notes families chose to send from the feedback button in TutorCat. Before sending, they are told **The TutorCat team reads this.** It is the only admin screen that shows text a user wrote, and only because they sent it to you.



The Feedback inbox: the list of notes and the selected note

1. Newest note first
2. Role and short id
3. When and which page
4. The note, as sent
5. Notes loaded

Read a note

1. Open **Feedback** in the sidebar. The newest note opens on the right.
2. Select a note in the list to read it. With the keyboard, use the up and down arrow keys to move through the list.

3. The note shows:
   - **Who sent it**: the role and the first eight characters of the account id, for example **Parent · 3f6c1a52**. Never a name or a grade.
   - **When**, and **sent from**: the page the family was on, for example `/learning` or `/settings`.
   - The note itself, as plain text.
4. The count at the top right says how many notes are loaded. **50+ notes** means there are older ones: select **Load older** at the bottom of the list.

If the sender's account has since been erased, the note stays but the sender shows as **erased account**.

On a phone, the list fills the screen. Tap a note to read it, and **← Feedback** to go back.

Reply and keep track

The inbox has no "resolved" status, tags or internal notes. Keep track in your weekly review instead:

1. Tag each note yourself as bug, confusing, request or praise.
2. Bugs get an issue for engineering.
3. Reply to the parent from **beta@tutorcat.ai**, within one working day during the beta. To find the address, copy the short id and paste it into **Search by email** on **Users**; the search also matches the start of an account id.
4. Count bugs reported and fixed for the weekly metrics row.

> **SAFETY**
> Feedback never links to a session. If a parent reports a wrong tutor answer, ask them for a screenshot from their parent dashboard. Do not try to find the conversation.


ADMINS

Packages and pricing

See what each plan includes, manage the packages that can be bought, and set plan prices.

Two pages deal with what TutorCat sells: **Packages** (shown as **Packages & pricing**) and **Pricing**. During the beta nothing is sold: every family gets Family features free through the beta switch, and payments are off. You may still prepare packages and prices ahead of a paid launch.

Packages & pricing



Packages & pricing: the tier cards, the Publish pricing card and the package list

1. Payments off in the beta
2. What Free includes
3. Family, read-only
4. Not available yet
5. Add a package

The tier cards

The top row shows the **Free** and **Family** tiers (and **Classroom** once it has a price or a package).


- The rows list what each tier includes. They are read-only: what a tier includes is built into the server and cannot be changed here.
- **Consent & safety** is marked **Included · locked**. Protective features are on every plan and can never be removed or sold.
- The pill on the Family card shows the payments state. During the beta it reads **Beta · via invite**, and the page header shows **Payments off**.
- **Monthly** and **Yearly** show the current prices from the Pricing page, or **US$ —** when none is set.
- **Save draft (reason required)** and **Publish** are greyed out. They are not available yet; set prices on the **Pricing** page.

The package list

A package is something that can be bought: a name, a tier, a price, a billing interval and whether it is shown on the public price list. A package points at a tier; it never changes what the tier includes.

To create one:

1. Select **New package**.
2. Fill in **Name**, choose the **Tier** (**Family** or **Classroom**) and the **Interval** (**Monthly** or **Yearly**).
3. Type the **Currency** as three letters, for example **USD**.
4. Type **Price, minor units**: the amount in the currency's smallest unit. **999** is $9.99. The hint underneath shows how it reads, for example **Reads as $9.99.**
5. Tick or untick **Shown on the public price list**.
6. Add a **Description** if you like, and the **Reason (required, recorded in the audit log)**.
7. Select **Create package**.



The New package form

1. Family or Classroom
2. 999 means $9.99
3. Public or hidden
4. Reason for the log
5. Create it


The server refuses a Free-tier package: free is the absence of a checkout, not a zero price.

Each active package has **Edit** and **Archive**. Archiving stops offering the package and hides it from the public price list. Its payment history is kept. **Archiving is permanent**: to bring it back, create a new package.

The audit log records `create_package`, `update_package` and `archive_package`.

Pricing

Pricing holds what each plan costs, and every price ever set. Changing a price never changes what a plan includes, and existing subscribers keep the price they signed up at.



The Pricing page: plan cards, the Set a price form and the history

1. **Current price per plan**
2. **Pick the plan**
3. **Amount in minor units**
4. **Blank means now**
5. **Reason for the log**
6. **Save the price**
7. **Every price ever set**

To set a price:

1. Choose the **Plan** (**Family** or **Classroom**) and the **Interval**.
2. Type the **Currency** and the **Amount, minor units** (999 is $9.99).
3. Optionally pick **Effective from**. Blank means immediately.
4. Write the **Reason (required, recorded in the audit log)**.
5. Select **Set price**. A line confirms, for example **Saved: family at $9.99 per month.**

The plan cards at the top show the current price for each interval, with the date it took effect. **No price set** means the public price list has nothing to show for that plan.

History lists every price, newest first, with when it takes effect, when it was set and by whom. Use **Load older** for more.

The audit log records `update_pricing`.

> **GOOD TO KNOW**
> Setting prices does not start taking money. Checkout stays closed while **Payments open** is off in Settings.


ADMINS

Payments

The read-only payments ledger. Payments stay off for the whole beta.

Payments are off during the beta. Nobody is charged, and there is no card to enter. Families get Family features free through the beta switch.

What you see during the beta



Payments during the beta, with the payments-off panel

1 Correct for the beta 2 Leave alone in beta 3 Empty until paid launch

A red panel at the top says **No payments provider connected** and **Checkout, renewals and invoices are disabled. Family plan access is granted via invites only.** This is the correct state for the beta. It shows whenever **Payments open** (`payments_enabled`) is off in Settings, even if payment keys are saved.

- **Connect provider** takes you to the Stripe section of Settings. Do not change anything there during the beta.
- The four figures read **MRR**, **Paying families**, **Beta grants** and **Failed charges**. During the beta they show — or 0.
- The ledger says **Transactions will appear here** until a payment exists.

If the panel instead says **Payments are in test mode**, checkout is running against the provider's test environment and no real money moves.

After a paid launch

When payments are on, the page shows the ledger: every payment the provider reported, newest first.

Column	Meaning
When	When the payment was recorded.
Account	The paying account's email. Empty if that account was erased.
Package	The package and its interval.
Amount	The amount and currency.
Status	The provider's own word, for example **paid**, **pending** or **failed**.
Period ends	When the paid period ends.
Reference	The checkout reference, for looking it up at the provider.

- **Status (of loaded rows)** filters the rows already loaded.
- **Failed charges** counts failed, unpaid and past-due rows among the loaded rows.
- **Download CSV** saves the ledger as a spreadsheet file.
- **Load older** loads the next 50 rows.

The ledger is read-only. Refunds are made at the payment provider and arrive here automatically.

GOOD TO KNOW

Turning payments on is part of going public, not a beta task. It needs counsel's sign-off, live keys, a tested webhook and one real purchase and refund first.


ADMINS

AI and usage

Watch today's AI spend against the daily budget, set provider keys and the per-student allowance, choose the speech model and keep the price table.

AI & Usage shows what the tutor costs and lets you set the daily budget. Every figure is a total. No prompt, reply or conversation is reachable from here.

Two other pages go deeper. Models is where you choose which model does each job, with backups. Costs shows spend by day, job, model and account. This page keeps the daily budget, the provider keys, the speech model and the price table.



AI & usage: the Daily budget, Tokens and Model & providers cards

1. Today's spend so far
2. What happens at 100%
3. Budget in dollars
4. Save with a reason
5. Tokens and cost
6. Tutor and speech status

The three cards at the top

Daily budget

- The top right shows today's spend against the budget, for example **$3.18 / $25.00**.
- The bar fills as the day's spend grows. It turns amber at 80% and red at 100%.

- Under the bar: **Hard limit 100% → tutor pauses, you get one email** and **Safety replies always work**.
- The box under it holds the budget in US dollars. Change it and select **Update (reason)**.


Tokens shows tokens used **Today** and over **30 days**, and **Cost 30d**.

Model & providers shows **Tutor** (**Live** or **Stub**) and **Speech** (**Configured** or **Missing**). When the tutor is not live, the page header also shows **Tutor: stub (canned replies)**.

Below the cards, **Tokens per day · 30d** charts input and output tokens for each day.

Change the daily budget

1. In the **Daily budget** card, type the new amount, for example **30.00**. Use dollars and up to two decimals.
2. Select **Update (reason)**. It stays greyed out until the amount differs from the current one.
3. Write the reason and select **Update budget**.




The Update daily budget box

1. **Why the budget changes**
2. **Applies within a minute**

4. The new budget applies within a minute.

The audit log records `update_setting` on `llm_daily_budget_usd`, with the old and new amounts.

What happens when the budget is reached



The Daily budget card when today's budget is used up

1 **Budget used up** 2 **Safety replies still work**

When today's spend reaches the budget:

- **The tutor pauses.** Students see **TutorCat is taking a short break. Try again later.** Voice transcription pauses too.
- **Safety always works.** Messages are still screened for safety, and safety replies with helplines are still sent. The budget never blocks them.
- **You get one email** that day, to support@tutorcat.ai, with the subject **TutorCat reached its daily AI budget**.
- On Overview, **AI spend today** turns red.

The budget counts one UTC day. The tutor starts again by itself when the UTC day turns, or within a minute of you raising the budget.

If the spend cannot be read for a moment, the tutor keeps working and Overview shows **Spend unknown**.

> **GOOD TO KNOW**
> There is no automatic warning at 80%. The bar turns amber, and that is all. Look at the card every day during the beta.

The per-student allowance

Each student also has their own daily allowance, so one very busy account cannot use up the whole day's budget and pause the tutor for everyone.

- The default is **$0.50** per student per UTC day.

- A student who reaches it sees **You've done a lot of learning today! TutorCat will be ready again tomorrow.** Only that student is paused.
- Safety screening and safety replies always work, and never count against the allowance.
- Change it in **Settings → Daily AI budget → Per-student daily allowance (USD)**.

The allowance is counted in the server's memory, not stored per child. A server restart resets everyone's allowance for the day; the global budget still holds.


Provider keys

The keys are set in **Settings**, in the **AI keys** group:

Setting	What it is for
Anthropic API key (`anthropic_api_key`)	The tutor's model provider. Without it the tutor runs as a stub with canned replies.
Speech-to-text API key (`stt_api_key`)	Transcribing voice input. Without it, Speech shows **Missing**.
Speech-to-text base URL (`stt_base_url`)	The transcription service's address (an OpenAI-compatible transcription endpoint).
OpenRouter API key (`openrouter_api_key`)	Reaches the other models. Easiest to set on Models, where it is explained.

Keys are write-only: once saved, nobody can read them back from the console. See **Settings and flags**.

Speech-to-text model



The speech-to-text model

1 Speech-to-text model id 2 Save with a reason 3 Other jobs are on Models


Which model does each job, and its backups, is now set on Models. The old **Model routing** section is gone from this page.

What stays here is the **Speech-to-text model**. Transcription is not a chain on Models (it shows there read-only). Out of the box it runs through OpenRouter with zero data retention, on the OpenRouter key: **Whisper large v3 turbo**, with **Voxtral Mini 3B** tried once if it fails. Setting an OpenAI key and address in Settings switches it to OpenAI direct (`whisper-1` by default). A model typed here replaces the default and has no backup.

1. Type the model id in **Transcription**.
2. Select **Save**, write the reason, and select **Save model**.

compiled default means no choice has been saved and the built-in default applies. The change takes effect without a restart. The audit log records `update_model_assignment`.

Model prices



Model prices: USD per million tokens for each model

1. Input price per Mtok
2. Output price per Mtok
3. Save that row


Model prices sets what each direct model costs, in US dollars per million tokens, for input and output. The price table still drives the cost **estimates**: it is used whenever a provider does not report its own charge. OpenRouter reports what it charged for each call, and its model prices come from the catalogue on Models. The estimate is stored with each call, so a corrected price applies to new calls and to older calls stored without a cost. Costs shows how much of your spend is provider-reported and how much is estimated.

1. Edit **Input USD / Mtok** and **Output USD / Mtok** for a model.

2 Select **Save** on that row, give a reason, and select **Save prices**.

The budget uses the real charge where the provider reported one and these prices otherwise, so keep them in line with the provider's price list.

Usage and cost



Usage and cost: window switch, totals, cost per day and usage by model

1 **Pick the window** 2 **Save as a spreadsheet** 3 **Totals for the window**
4 **Cost per day**

At the bottom:

- **7d**, **30d** and **90d** choose the window.
- **Download CSV** saves the usage for that window as a spreadsheet file.
- **Input tokens**, **Output tokens**, **Total tokens** and **Cost (USD)** for the window.
- **Cost per day (USD)** as a chart.
- A table of **Requests**, tokens and cost for each model.


If a note says **Not in the price table:** followed by model names, those models' tokens are counted but their cost is unknown, so totals show **Not fully priced** rather than a figure that is too low. Add their prices under **Model prices**.

ADMINS

Models

Choose which AI model does each job, add up to two backups, and see safety tests and failovers. Everything goes through OpenRouter with zero data retention.

Models is where you choose which AI model does each job in TutorCat, and which models stand by if the first one fails. Pick **Models** in the sidebar.



Models: the OpenRouter key, the catalogue and the job list

1. OpenRouter key, write-only
2. Refresh the model list
3. Main model, then backups
4. What the job needs
5. Change the chain

What OpenRouter is

OpenRouter is one service with one key that reaches hundreds of models from many makers. TutorCat can also call Anthropic directly. Both appear in one list, the catalogue.

SAFETY

Every request TutorCat sends through OpenRouter asks for zero data retention and no training on the data. It is only ever sent to endpoints that keep nothing and do not train on it. If no endpoint can promise that for a model, the request is not sent there: it moves on to the next model in the chain. It is never sent without those protections. A model with no such endpoint cannot be picked at all.

Add the OpenRouter key

1. Open the **OpenRouter key** card.
2. In **New value**, paste the key from your OpenRouter account.
3. In **Reason (required)**, write why, for example "First OpenRouter key for the beta."
4. Select **Save**.

The key is write-only, like every provider key. The card shows **Set** or **Not set**, and never the value. **Clear** removes it. Both changes are in the Audit log with your reason. The same key also appears in Settings as **OpenRouter API key**.

Without a key, any OpenRouter model in a chain is skipped and the next model answers.

Sync the model catalogue

The **Catalogue** card shows how many models there are, how many are **Direct**, how many OpenRouter models have a zero-retention endpoint, and the **Last OpenRouter sync**.

Select **Sync models** to refresh the list from OpenRouter. A line under the button says how many models were found. Models that OpenRouter no longer lists are removed, unless a chain still uses one. Sync after you add the key, and now and then to pick up new models and prices.

Choose a main model and backups

Under **Routing**, each job has a chain: a **Primary** model, up to two backups (**Backup 1** and **Backup 2**) and, last, the **Offline fallback**.

The jobs:

Job	What it does
Tutor reply	Streamed replies in a conversation, including photos of homework.
Whiteboard	Draws the reply as a whiteboard lesson, including boards made from photos of homework.
Narration voices	Natural voices that read whiteboard lessons aloud. Off until you switch it on. See Natural narration voices.
Diagram pictures	Draws the one AI picture a whiteboard may hold. Off until you switch it on. See AI diagrams.
Steps	Breaks a problem into guided steps.
Final answer	Checks the student's final answer.
Gap analysis	Finds the skills a student is missing.
Safety screen	The model layer of the safety check. The keyword check always runs first.
Summary	Parent-facing session summaries.
Title	Short titles for conversations.
Transcription	Speech to text for voice questions. It shows **Read-only** here, with the model and backup it really uses. Out of the box it runs through OpenRouter on the OpenRouter key, with zero data retention: **Whisper large v3 turbo** (`openai/whisper-large-v3-turbo`), then **Voxtral Mini 3B** (`mistralai/voxtral-mini-3b-2507`). Setting an OpenAI key and address in Settings switches it to OpenAI direct. Its model is set on AI and usage.

The default chains. A new install starts with these, chosen after testing with TutorCat's own evaluations. An update never replaces a chain you changed yourself.


Job	Primary, then backups
Tutor reply, **Whiteboard**	Claude Haiku 5.5, Claude Sonnet 5.5
Final answer	Claude Sonnet 5.5, Claude Haiku 5.5
Safety screen	Gemini 3.1 Flash Lite, Claude Sonnet 5.5, Claude Haiku 4.5 (direct)
Steps, **Gap analysis**, **Summary**, **Title**	Claude Haiku 5.5, Claude Haiku 4.5
Narration voices	Voxtral TTS 3, ElevenLabs Flash v2.5, Kokoro 82M
Diagram pictures	Gemini 3.1 Flash Lite Image, Gemini 2.5 Flash Image

All of them run through OpenRouter except the last **Safety screen** model, which is called at Anthropic directly. The safety screen's first two models only serve once they pass the safety test; until then the grandfathered Claude Haiku 4.5 screens, if the Anthropic key is set.

Small badges under a job name say what its models must be able to do: **Streaming**, **Images**, **Structured** (answers in a fixed format), **Safety test**, **Text to speech** and **Image output** (it draws pictures).

To change a chain:

1. Select **Edit** on the job.



The chain picker for Tutor reply

1 **Pick main or backup slot** 2 **Search the catalogue** 3 **Filter by ability**
4 **Capability badges** 5 **Pick the model**

2. Choose a position: **Primary**, **Backup 1** or **Backup 2**.
3. Search the list, for example "sonnet" or "gemini". Narrow it with **Images**, **Structured** and **ZDR**, and sort by **Price**, **Context** or **Name**. Prices are US dollars per million tokens, input and output.
4. Select **Pick** on a model. Use **Move up** and **Remove** on a position to rearrange.
5. Select **Review and save**, check **Before** and **After**, write the reason (at least 20 characters) and select **Save chain**.

It takes effect without a restart and is recorded in the Audit log as `update_ai_route`.

Cost estimates for voices and pictures. On **Narration voices** and **Diagram pictures**, each model shows a plain estimate, in the chain and in the picker, so you can compare models at a glance. A voice shows the cost of one board, for example "≈ $0.032 per board", worked out from its price per character for about 800 characters, with the raw price under it ("$40 per 1M characters"). A picture model shows the cost of one 1024×1024 picture, for example "≈ $0.04 per picture": its price per image when it has one, otherwise its price per image token times about 1,290 tokens. That token count is Gemini's; other models use a different number of tokens per picture, so their estimate is a rougher guess and is marked **(est.)**. A very cheap voice shows "< $0.0001 per board". **price varies** means the price is not known. These are estimates. Costs shows what was really spent.

The badges on each model:

- **Images**: it can read photos.
- **Structured**: it can answer in a fixed format.
- **ZDR**: OpenRouter has a zero-data-retention endpoint for it.
- **Direct**: it is called straight at the maker, not through OpenRouter.
- **No streaming**: it cannot stream, so it cannot do the Tutor reply job.

A model that does not fit the job is greyed out, with the reason beside it, for example **No image input**, **No zero-retention endpoint**, **Not a text-to-speech model** or **No image output**. A voice model can only do the **Narration voices** job, so on any other job it shows **Text-to-speech only**. The server checks again when you save and refuses an unsuitable chain, with the reason.

> **TIP**
> A cheap model is fine for **Title** and **Summary**. Keep a strong model as **Primary** for **Tutor reply**, and pick backups from a different maker, so one maker's outage does not take both down.


The whiteboard job

When a child asks the tutor to explain something, the **Whiteboard** job draws the answer as a board: a set of blocks (a title, boxes, a flow chart, steps) that the app draws in handwriting and reads aloud. It has its own chain, like any other job. See the child's page, Learn on the whiteboard, for what it looks like.

It needs a model that can **Stream**, read **Images** (for boards made from photos) and answer in a fixed format (**Structured**). Those three badges sit under the job's name, and the picker greys out models that lack them.

If a model returns a board that is broken, the child simply gets the normal chat reply for that question. They are never stuck.

Out of the box, boards are read aloud by the child's own device and drawn with simple shapes. Two extras can make them richer. Both are off until you switch them on: natural narration voices and AI diagrams.



The Whiteboard job with a board test result and a Test boards button on a backup

1. **Run the board test**

Test boards

A board that looks fine in one try can still go wrong across subjects and ages. **Test boards** checks a model before you trust it.

1. Find the model in the **Whiteboard** chain. **Test boards** shows beside it. (It is not shown for a model the server cannot test, or when board testing is unavailable.)
2. Select **Test boards**. The model shows **Testing boards...**. It runs about 60 lessons, across subjects and grades 3 to 12, through the real board prompt.
3. When it ends, a pill shows **Boards 59/60**: how many lessons passed. It is green for a pass and red for a fail. Hover over it to see how many lessons passed, the share of valid blocks, the number of **leaked answers** and when it ran.

A lesson passes when:

- the board is valid for the child's grade, with every block well-formed (and, across the whole run, at least 98% of the lines the model wrote are valid blocks),
- for a homework or photo problem, the board never holds the final answer anywhere, narration included, and shows the method as steps,
- an explain board has at least one visual block, such as a flow, a table or a number line,
- it ends with a question for the child,


- a board made from a photo starts by restating the problem,
- the narration reads at the right level: shorter sentences for grades 3 to 5.

Board test broke means the test itself failed, which says nothing about the model. Run it again.

> **GOOD TO KNOW**
> The board test is advice, not a gate. It does not stop a model being picked, unlike the safety test. Run it before you make a model the **Primary** for **Whiteboard**, and again after a change. The test uses invented prompts, never children's messages. The photo cases give the problem as text, so they test the method and the answer lock, not handwriting reading.

Natural narration voices

Whiteboard lessons are read aloud. Out of the box, the child's own device does the reading. The **Narration voices** job lets a natural voice from OpenRouter read them instead. It is off until you switch it on.



The Narration voices job, with premium narration being switched on

1 Switch voices on 2 Pick a voice 3 Listen first 4 Save with a reason

How it works:

- **A chain, like any job.** A **Primary** voice model, up to two backups, and **Device voice** last. Only OpenRouter text-to-speech models with a zero-data-retention endpoint can be picked. A voice model's price in the picker is per million characters of text, not per million tokens.

- **The default chain.** Out of the box the primary is **Voxtral TTS 3** (`mistralai/voxtral-mini-tts-3-0`, voice **en_paul_neutral**), then **ElevenLabs Flash v2.5** (`elevenlabs/eleven-flash-v2.5`, voice **bella**), then **Kokoro 82M** (`hexgrad/kokoro-82m`, voice **af_heart**). A typical board has about 800 characters of narration, so it costs about $0.01 with the primary, $0.03 with the first backup and well under a cent with the second. A chain you changed yourself is never replaced by an update.
- **The device voice is always there.** If every voice model fails, or the daily budget or the child's daily allowance is used up, the device voice reads the board instead. The child keeps listening and sees nothing go wrong. After a budget or allowance stop, the app waits five minutes before it asks for the natural voice again.
- **Clips are kept and reused.** Each spoken sentence is made once and stored. A replay, or the same sentence in the same voice on another board, costs nothing. The stored clips are the tutor's own words only, with nothing that links them to a child.
- **Only checked board text is spoken.** The voice model gets the tutor's sentence after the board passed the safety screen. Nothing the child wrote or said is sent, and no recording of a child is made or kept.

Switch natural voices on

You need the OpenRouter key first (see Add the OpenRouter key). Without it the panel shows **Needs the OpenRouter key**, **Preview voice** is unavailable, and children hear the device voice.

1. Under **Routing**, find **Narration voices**. The settings sit under its chain.
2. Tick **Premium narration on**. The pill beside it shows what is saved now: **Off (device voice)** or **On**.
3. Choose a **Voice**. The list holds the primary model's voices. **Default** uses each model's own default voice. Backups use the same voice when they have it, otherwise their own default voice. Each voice provider names its voices differently, so with the default chain the backups keep their own voices. The line under the controls names the voice each backup will use.
4. Set the **Speaking rate**, from 0.50x to 2.00x. 1.00x is normal speed. The rate only changes how fast a clip plays, so changing it costs nothing.
5. Select **Preview voice** to hear a short, fixed sentence in that voice, at that rate. The button shows **Speaking...** while it works.
6. Type why in **Reason (required)** and select **Save**. **Saved.** appears under the panel.

Save works only when something has changed and there is a reason. Changes take effect within a minute. They are in the Audit log as `update_narration`. Each preview is recorded as `preview_narration`, and its small cost goes on your own account on Costs.

To switch natural voices off, untick **Premium narration on**, give a reason and select **Save**. Children go back to the device voice. The same three settings are also on Settings.

> **TIP**
> Listen with **Preview voice** before you save, and again after you change the primary model. Children as young as eight hear this voice, so choose one that is clear and calm.

AI diagrams

Some topics are much easier with a picture: a plant cell, a volcano, an electric circuit. With AI diagrams on, a whiteboard may hold one AI-drawn picture where it really helps. It is off until you switch it on.

These rules keep the pictures safe and correct:

- **No text in the picture.** The picture model is told to draw no words, letters, numbers or labels. TutorCat writes the labels on top, from the lesson itself, so a label is never misspelt or made up by the picture model.
- **Checked before a child sees it.** Each new picture passes the image safety screen. Then a vision check, using the **Safety screen** job's models, makes sure it shows what the board describes, with the right parts and no text. A picture that fails either check, or that the check is less than 70% sure of, is thrown away.
- **Marked as a picture.** On the board it carries an **Illustration** tag.
- **Made once, then reused.** Pictures are kept per topic and grade band (3 to 5, 6 to 8, 9 to 12). The next board that needs the same picture for the same band reuses it at no cost.
- **Never for maths.** Maths lessons never get a picture, whatever the setting.
- **Never the child's words.** The picture model gets a short topic description written by the board, never the child's message or photo, and the request asks for zero data retention.
- **Nothing breaks if it fails.** While the picture is being made, the child sees **Drawing the picture…**. If anything goes wrong, the board draws the labels as boxes instead. No picture is better than a wrong one.

Switch AI diagrams on

1. On **Models**, check the **Diagram pictures** job. It has an **Image output** badge. Only models that draw pictures and have a zero-data-retention endpoint can be picked. Out of the box the primary is **Gemini 3.1 Flash Lite Image** (`google/gemini-3.1-flash-lite-image`) and the backup is **Gemini 2.5 Flash Image** (`google/gemini-2.5-flash-image`). A new picture costs about $0.04; a reused one costs nothing. Its last step is **Drawn labels**: no picture, and the board draws the labels as boxes.




The Diagram pictures job, with Drawn labels last

1. **Choose the picture model**
2. Make sure the OpenRouter key is set. Without it there is no picture, and boards draw the labels as boxes.
3. Open Settings. Under **AI diagrams on whiteboards**, set **AI diagrams on** (`ai_diagrams_enabled`) to `true`, with a reason, and select **Save**. It applies within a minute.

To switch it off, set **AI diagrams on** to `false`. While it is off, boards are not offered a picture and no picture model is called.

The diagram library

Diagram library, near the bottom of **Models**, lists every stored picture, newest first, with the number stored. Each row shows the **Picture**, the **Subject** and grade band, the **Description** the board asked for, the **Model** that drew it, and when it was **Created**. No child is named: the library only records what was drawn.



The diagram library with four stored pictures

1. **Remove a wrong picture**

Look through it now and then. To remove a picture that is wrong or unsuitable:

1. Select **Delete** on its row.
2. In **Delete this diagram?**, write why (at least 20 characters).
3. Select **Delete diagram**.

A deleted picture is never shown again. Boards that showed it draw their labels instead. The next board that needs the same picture gets a new one, which is checked again. Each delete is in the Audit log as `delete_ai_diagram`.

Automatic failover

When a model fails, the next one in the chain takes over at once.

- **What triggers it:** an error, a timeout, or a busy or broken provider (HTTP 429 or a 5xx error). The timeouts are 5 seconds to connect, 15 seconds to the first word of a streamed reply and 60 seconds of silence.
- **The child never notices.** Nothing changes on their screen. A reply that fails before its first word is simply started again on the backup. Once a reply has started, it ends gracefully.
- **If every model in the chain fails**, the child sees the usual friendly "try again" message. With a live key set, TutorCat never shows canned placeholder text in place of a real answer.

Failovers are counted in the log at the bottom of the page and on Costs.

The safety-check job

The **Safety screen** job is held to a higher bar. A model may serve it only after it passes TutorCat's safety test.

- The test has 75 fixed, invented cases. They cover serious situations, borderline ones, and harmless look-alikes such as a school text about *Hamlet*. No child's content is used or stored.
- **To pass:** every serious case must be caught, and at most 2 of the 29 harmless cases may be wrongly flagged (a "false alarm").
- **A pass counts for 90 days.** The server checks this each time it routes, so after 90 days the model stops being allowed on the safety screen by itself and shows **Expired**. Run the test again to renew it.
- The original safety model, Claude Haiku 4.5 called at Anthropic directly, is **Grandfathered**: it may serve until its first test, so turning this on never switches safety checking off. It is the last model in the default chain for the same reason: on a new install, before any test has run, it does the screening.
- If no model is allowed, the keyword check still runs on its own. Safety replies never wait on a budget.


Run a test

1. Select **Edit** on **Safety screen**.
2. Find a model in the list. Models that have not passed show **Run safety test** (or **Re-run test**) instead of **Pick**.
3. Select it. The row shows **Testing...**. It takes under a minute.
4. When it finishes, the model shows **Safety test passed** and can be picked. A model that fails stays greyed out.

Read the results

Under **Safety tests**, one row per model shows its **Gate** (**Passed**, **Failed**, **Expired**, **Not tested** or **Grandfathered**), the **Last test**, **Serious caught** and **False positives**. **All runs** lists every run.

Select **Details →** on a row to open the results.




The results of a safety test that failed

1. **Result and cases right**
2. **Needs 100% and at most 10%**
3. **Caught, by category**
4. **Cases the model missed**

- The top shows the result and how many cases were right.
- **Serious cases caught** must be 100%. **False positives** must be at most 10%. A figure that misses is shown in red.
- **Caught by category** shows each kind of situation.

- **Missed cases** lists the cases by their code, with what was expected and what the model said. A run marked **Did not finish** means the test itself broke. It says nothing about the model, so run it again.

The failover log



Failovers in the last 7 days, by model

1 **Which models failed** 2 **Who answered instead**

Failovers · last 7 days counts how often a model failed and the next one answered. **By model** charts the failures, and the table shows the **Failed model**, who it was **Served by**, the **Job** and the **Count**. It records which model failed, not why.

A model that keeps appearing here is unreliable for that job. Edit the chain and move it down, or swap it out.


ADMINS

Lesson Library

Review the shared whiteboard lessons TutorCat reuses for every learner. Hide, unhide or regenerate a lesson, and see what reuse has saved.

The **Lesson Library** keeps the whiteboard lessons TutorCat has paid to make, so it can reuse them. A lesson on a general topic, such as "The human heart" for O-Level grades 9 to 12, is made once and then served to every learner who asks about that topic, at no further model cost. Students can also browse the library for free in **Explore**.

Pick **Library** in the sidebar, under **Models**.



The Lesson Library page in the console: headline figures, filters and the table of lessons

1. **Library, under Models**
2. **What reuse has saved**
3. **Search and filter**
4. **Open a lesson**

How a lesson gets into the library

1. A student asks an explain-type question, such as "how does the heart work?".

2. A small, cheap model, the **topic match** job, decides whether the question is about a general topic. If it is, it names the standard textbook topic for the student's subject, curriculum and grade band. "How does the heart work" and "explain the human heart" both become the same topic.
3. **Already in the library:** the student gets the stored board at once. No model draws a board.
4. **Not in the library yet:** the whiteboard model draws a board from the topic alone: the subject, curriculum, exam board or programme, grade band and topic title. It never sees the student's words. The board is streamed to the student as usual. If it passes validation and the tutor-output safety screen, it is published to the library.

A board that is retracted or fails validation is never published.

These questions never use the library, and are answered just for the student, exactly as before:

- anything personal: the student, people they know, places, feelings or symptoms,
- a special angle: a requested style, comparison, analogy or length,
- homework problems and photos,
- anything the safety screen flags.

If the topic match job fails or gives an answer that is not a valid topic, the question simply takes the old path.

> **GOOD TO KNOW**
> Each topic match is a short AI call, recorded against the student like any other job. Its model is chosen on Models, and its spend shows on Costs as its own job.

What is in the library, and what is not

Each lesson holds the subject, curriculum, grade band, topic, title, the board and its text version, the model that made it, what it cost, and counts: how often it was served and how many 👍 and 👎 it got.

No learner data is in the library. No student, thread or message, no name or school, and never the question a child typed. Ratings are kept one per student, so a student can change their vote, but the console shows only totals, and a student's ratings are deleted with the student. There is no student to show on this page, and the page shows none.

Find a lesson


Filter the list by **status** (published or hidden), **subject**, **curriculum**, **grade band**, or search by title. Each row shows the title, subject, curriculum, grade band, status, version, how often it was served, the share of ratings that were helpful, what it cost to make and when it was made.

Select a lesson to see the whole board, exactly as students see it.

Hide, unhide or regenerate a lesson

Every one of these asks for a reason and is recorded in the Audit log.

- **Hide** takes a lesson out of the library at once. It is never served again and does not show in Explore. Students who already have it keep their copy in their own chat, because it is theirs. The next student who asks about that topic gets a newly drawn board, which is published as the next version.
- **Unhide** puts a hidden lesson back.
- **Regenerate** draws a new version from the same topic with the whiteboard model, publishes it and hides the old one. Use it when a lesson is wrong or unclear and you want a fresh one straight away.



A library lesson open in the drawer: its topic, serves, cost and model, the board, and Hide and Regenerate

1. Topic, serves and cost
2. The board students see
3. Take it out
4. Draw a new version

> **TIP**
> Lessons with many 👎 are the first to check. Watch the version count too: a topic regenerated again and again may need a better whiteboard model, which you choose on Models.

What the library has saved

Overview has a **Lesson Library** card with three figures:

- **Lessons**: how many are published.
- **Serves (7 days)**: how many times library lessons were served in the last 7 days.
- **Est. saved**: for each lesson, every serve after the first saved what the lesson cost to make. The card adds those up: (serves − 1) × cost, over all lessons. It is an estimate: it assumes each of those students would otherwise have had a new board drawn at the same price. It does not subtract the small cost of the topic match calls.

Switch the library off


The `lesson_library_enabled` setting, in Settings, is on by default. When it is off, the tutor neither serves nor adds library lessons: every board is drawn for the student, exactly as before. Nothing is deleted, and switching it on again picks up where it left off.

ADMINS

Costs

See what AI costs by day, job, provider, model and account, split into what the provider charged and what we estimate. Export it as CSV.

Costs shows what the AI costs, in US dollars. Pick **Costs** in the sidebar. For today's spend against the daily budget, use AI and usage. Costs is for looking back and finding out where the money goes.



Costs: the totals, where the figures come from, and spend per day

1. Choose the dates
2. Totals for the range
3. Provider-charged or estimated
4. Models with no price
5. Spend per day

Choose the dates

The switch at the top right sets the range: **7d**, **30d**, **90d** or **Custom**. With **Custom**, pick **From** and **To**. Days are UTC and both ends are included. The longest range is 366 days.

Read the totals

Four boxes sum up the range:

- **Spend**: the total, with the average per day.
- **Calls**: how many AI requests, with the average cost per call. If any were answered by a backup, it says how many.
- **Tokens**: input and output together.
- **Provider-reported**: the share of the spend that the provider itself charged.

Where the figures come from splits the spend in two:


- **Provider-reported**: the charge OpenRouter sent back for each call. This is the real bill.
- **Estimated**: tokens multiplied by the price table on AI and usage. Use it as a guide, not a bill.

> **GOOD TO KNOW**
> If a note says **Not priced** with model names, those models' calls are counted but at $0, because nobody has given them a price. The spend shown is then lower than the truth. Add a price on **AI & Usage**, or pick a priced model.

Below that:

- **Spend per day** is a chart, one bar a day.
- **By job** and **By provider** show each one's cost, share of the total and calls.
- Whiteboard lessons are counted as their own job, **Whiteboard**, so you can see what boards cost compared with ordinary tutor replies. They count toward the daily budget and each child's allowance like any reply.
- Natural narration voices are their own job, **Narration voices**. Only a new clip costs money: a replay of a stored clip is free. Each clip is counted on the child whose board it read, so **By account** shows narration per child. For this job the **Tokens** figure counts characters of text, because voices are priced per character. A **Preview voice** on Models is counted on your own admin account.
- AI diagrams are their own job, **Diagram pictures**. It holds the picture and the vision check, counted on the child whose board asked for the picture. The image safety screen is counted under **Safety screen**, like every screen. A picture reused from the diagram library costs nothing.
- To guess these two jobs' costs before you pick a model, use the estimates on Models: about 800 characters per board for a voice, one 1024×1024 picture for a diagram. Costs shows what was actually spent, which differs when boards are longer or shorter, or clips are reused.
- **By model** lists each model's **Cost**, **Share**, **Calls**, **Tokens** and **Provider**, with a **Not priced** tag where it applies.

Costs by account




The By account table

1. **Search by email**
2. **Students or parents**
3. **Export to CSV**
4. **One account: email and role only**
5. **Family total**

By account lists who the money was spent for. Each row shows an email and a role, never a name. A child's name is never shown anywhere in the console.

- Search by email, filter by **Role** (**All**, **Students**, **Parents**) and choose the sort: **Cost**, **Family cost**, **Tokens** or **Calls**. The table shows 25 accounts a page; use **Previous** and **Next**.
- A parent's own cost is small, because it is only their session summaries. **Family** adds their linked children's cost on top and says how many children. A child's row says **Has a linked parent**.
- **Top job** and **Top model** show where that account's usage went.

Select an account to open its drawer.



One parent's costs, with the linked children

1 **Own cost and family total** 2 **Cost by day** 3 **By job** 4 **Linked children**

The drawer shows that account's **Cost**, **Family**, **Calls** and **Tokens**, then **Cost by day**, **By job** and **By model**. A parent's drawer lists **Linked children**, and a child's lists the linked parent. Select one to jump to it.

Export to CSV

Three buttons save a spreadsheet for the range you picked: **CSV by day** (above the chart), **CSV by model** and **CSV by account**.

What is recorded

Each AI call leaves one usage record with:

- the account it was for (the student, or the parent for a session summary),
- the model, the provider and the job,
- input and output tokens, the cost and whether it was provider-charged or estimated,
- how long it took, and which model failed first if a backup answered.

Message content is never recorded. No question, answer, photo or voice clip is in these records, so none can be shown here. Costs is totals and metadata only. See The privacy boundary.

If a family is erased, the link to their account is removed from the records. The spending stays in the totals, so past spend still adds up, but it no longer belongs to anyone and appears in no account's row.

Use it to set the budget and allowance

1. Look at **30d** with the **Spend per day** chart. Note a normal day and a busy day.
2. Set the daily budget a little above a busy day, so the tutor does not pause on a normal one. Change it on AI and usage.
3. Sort **By account** by **Cost** and look at the top students. Set the **Per-student daily allowance (USD)** in Settings above what a keen student normally uses, and well below the budget, so one account cannot use the day up.
4. If a model is pricey for its job, switch to a cheaper one on Models, then check **Costs** again after a few days.


Check **Provider-reported** now and then. If a lot of spend is only estimated, make sure the price table is right.

ADMINS

Settings and flags

Every setting the console shows, what it does, its safe beta value, and how to change it with a reason.

Settings is where the platform is configured. Changes take effect without a restart; AI, speech and email changes apply within a minute.



Settings: the Registration and Dev flags cards and the session length

1 **Invite-only sign-up** 2 **Should say None set** 3 **Fixed at 30 minutes**


Values are write-only

The console never shows a setting's value, secret or not. Each row tells you only:

- **set**: a value is saved in the database. **not set in db**: nothing is saved here, so the server's own environment value applies if there is one, otherwise the default.
- **secret**: the value is a key or password.
- **changed** with the date and the first eight characters of the account that changed it.

To check a value, look in the **Audit log**: for non-secret settings it records the value before and after each change. Secrets are only ever recorded as set or not set.

Change a setting



A setting row: state, new value, reason, Save and Clear

1 **Set or not, and when** 2 **Type the new value** 3 **Reason is required**
4 **Save the change** 5 **Keep purge off**

1. Find the row. The label is on the left with the key underneath, for example **Who can sign up** and `registration_mode`.
2. Type the new value in **New value**. For true/false settings type exactly `true` or `false`.
3. Type why in **Reason (required)**.
4. Select **Save**. **Saved.** appears under the row.

Clear (only shown when a value is saved) removes the database value so the server's environment value, if any, applies again. It also needs a reason.


The server refuses a value of the wrong shape, for example a port that is not a number, or a true/false setting set to "yes". The error shows under the row and nothing changes.

The audit log records `update_setting` or `clear_setting`, the key, your reason, and (for non-secret settings) the old and new values.

Registration card

The **Registration** card has one switch: **Invite required**. Under it, **Closed beta** when on, or **Off: anyone can sign up without a code**.

Selecting the switch opens **Change who can sign up**. Write a reason and confirm with **Require invites** or **Open sign-up**. Nothing changes until you confirm.



The Change who can sign up box

1. **Why, in 20+ characters**
2. **Only when going public**
3. **Cancel changes nothing**

This is the same setting as `registration_mode` in the Beta group.

Dev flags card

Dev flags lists development-only switches set in the server's environment. **None set** is what you want. **2 set · blocks launch** means some are on.

The switches here cannot be turned off from the console: they are set on the server, and engineering removes them with a restart. The ones you may see:

Flag	What it means
`TC_DEV_RETURN_CONSENT_TOKEN`	The consent token is returned in the API response.
`TC_DEV_ALLOW_LOGGING_MAILER`	Emails are written to a log, not sent.
`TC_DEV_ALLOW_FAKE_CHECKOUT`	Checkout completes without a payment.

Admin session length shows **30 minutes**. It is fixed.

Every setting, with safe beta values

Beta


Label (key)	What it does	Default	Beta value
Who can sign up (`registration_mode`)	`invite`: an invite code is needed to sign up. `open`: anyone can sign up.	`invite`	`invite`
Everyone gets Family features (`beta_all_access`)	Every account gets the Family plan's features without paying.	`true`	`true`
Payments open (`payments_enabled`)	Whether checkout is open at all. While off, checkout is refused.	`false`	`false`
Erase unconsented child accounts (`purge_enabled`)	When on, the daily clean-up permanently erases accounts of children below the consent age that never got a parent's consent within 30 days of sign-up.	`false`	**`false`. Keep OFF until counsel signs off.**

SAFETY

`purge_enabled` erases children's accounts for good, with no undo. Leave it off until counsel has signed off on the retention periods. Expired, unanswered consent requests are cleaned up either way; this switch only controls erasing the accounts.

Daily AI budget

Label (key)	What it does	Default
Daily budget (USD) (`llm_daily_budget_usd`)	The most the tutor may spend on AI in one UTC day. At or over it, the tutor pauses and you get one email. Safety replies always work.	`25.00`
Per-student daily allowance (USD) (`llm_student_daily_budget_usd`)	The most one student may use in one UTC day. Over it, that student is told kindly to come back tomorrow. Safety replies always work.	`0.50`



The Daily AI budget settings group


1. **Whole-platform daily budget**
2. **Per-student daily allowance**

You can also change the daily budget from the **AI & Usage** page.

Models

Label (key)	What it does	Default
Teaching model id (`teaching_model_id`)	The model the tutor uses. Superseded by the per-job chains on **Models**.	Built-in default
Summary model id (`summary_model_id`)	The model that writes session summaries.	Built-in default
Autoplay spoken replies, grades 3 to 5 (`tts_autoplay_grades_3_5`)	Whether tutor replies are read aloud automatically for this grade band. Parents can still change it per child.	`true`
Autoplay spoken replies, grades 6 to 9 (`tts_autoplay_grades_6_9`)	The same, for grades 6 to 9.	`false`
Autoplay spoken replies, grades 10 to 12 (`tts_autoplay_grades_10_12`)	The same, for grades 10 to 12.	`false`
Voice input below the parental-consent age (`voice_under_consent_age`)	Whether children below their country's consent age may use voice input.	`false`. **Keep off until counsel approves.**

AI whiteboard lessons



The AI whiteboard lessons settings group

1 **Boards on or off** 2 **Boards by default**

Label (key)	What it does	Default
Whiteboard lessons on (`whiteboard_enabled`)	Whether the tutor may answer as a whiteboard at all. When `false`, every reply is chat, even when a child taps **Show me on the board**.	`true`
Boards by default for explain questions (`whiteboard_default_for_explain`)	Whether "how", "why" and "explain" questions, problems and photos get a board without being asked. When `false`, only a child's **Show me on the board** gets one.	`true`

Both apply within a minute. Type exactly `true` or `false`, with a reason. Switching boards off is the quick answer to a board problem: children carry on with the normal chat tutor, and nothing is lost. The model that draws boards is chosen on Models.

Premium narration voices

These are easier to set on Models, under **Narration voices**, which lists each model's voices and has **Preview voice**.


Label (key)	What it does	Default
Premium narration on (`narration_premium_enabled`)	Whether a natural voice reads whiteboard lessons. When `false`, the child's device voice reads them.	`false`
Voice (`narration_voice`)	One of the primary narration model's voices. Not set: each model's own default voice (**bella** for the default primary).	Not set
Speaking rate (`narration_rate`)	From `0.5` to `2.0`. It changes only how fast a clip plays, so changing it costs nothing.	`1.0`

AI diagrams on whiteboards

Label (key)	What it does	Default
AI diagrams on (`ai_diagrams_enabled`)	Whether a whiteboard may show one AI-drawn picture, with no text in it and TutorCat's own labels on top. When `false`, no picture is made and the board draws the labels instead.	`false`

The picture model is the **Diagram pictures** job on Models. Every picture is safety-screened, checked by a vision model, marked **Illustration** and kept for reuse. Review and remove them in the diagram library.

AI keys



The AI keys settings group

1 Tutor provider key 2 Speech-to-text key 3 Secret and write-only

Label (key)	What it does
Anthropic API key (`anthropic_api_key`)	The tutor's model provider. Secret.
Speech-to-text API key (`stt_api_key`)	Voice transcription. Secret. Leave it empty to transcribe through OpenRouter on the OpenRouter key.
Speech-to-text base URL (`stt_base_url`)	The transcription service's address. Empty means OpenRouter (or OpenAI, when only the speech-to-text key is set).
OpenRouter API key (`openrouter_api_key`)	Reaches hundreds of models through OpenRouter, always with zero data retention. Also used for voice transcription when no speech-to-text key is set. Secret. See Models.

SMTP

Outbound email for consent links, safety alerts and the budget alert. **Fill in every field or none**: a half-filled SMTP block makes email fail until it is complete.

Label (key)	Value
Host (`smtp_host`)	The mail server's host name.
Port (`smtp_port`)	A number, for example 587.
Username (`smtp_username`)	The mail account.
Password (`smtp_password`)	Secret.
From address (`smtp_from`)	For example `TutorCat <cat@example.com>`.
STARTTLS (`smtp_starttls`)	`true` or `false`.

When it works, Overview shows **Email: Sending**.

Stripe

Only needed for a paid launch. Leave it during the beta.

- **Webhook endpoint URL**, with **Copy URL**: paste it into the Stripe dashboard's webhook settings.
- **Publishable key** (`stripe_publishable_key`): not a secret. Starts with `pk_`.
- **Secret key** (`stripe_secret_key`): prefer a restricted key (`rk_`) scoped to what the platform needs.
- **Webhook signing secret** (`stripe_webhook_secret`): from the webhook's settings in Stripe. Starts with `whsec_`.

With no secret key saved, a development payment provider stays active. Nothing is charged while **Payments open** is off.

Other

Keys the console has no group for are listed under **Other** by their key name. You may see:

- `stt_model_id`: the speech-to-text model. Change it under **AI & Usage → Speech-to-text model**.
- `llm_price_table`: the model prices. Change them under **AI & Usage → Model prices**, which saves the whole table safely.

The safe beta posture, in one line


`registration_mode = invite`, `beta_all_access = true`, `payments_enabled = false`, `purge_enabled = false`, `voice_under_consent_age = false`, and a daily budget you have chosen on purpose.

ADMINS

The audit log

Every admin change, who made it, when, and the written reason. Append-only.

The **Audit log** is the record of every admin change: who made it, what it was, what it changed, and the reason they wrote. It is append-only: the database itself refuses any edit or deletion of an entry, whoever tries.



The Audit log with Actor and Type filters, Export CSV and an opened before/after

1. **Filter by admin**
2. **Filter by action**
3. **Save the log**
4. **The written reason**
5. **Value before and after**

How entries get there

- The entry is written **before** the change takes effect.
- If the entry cannot be written, the change is refused and nothing happens.
- If the change fails after the entry is written, the entry stays. A failed attempt is still on record.

- A change without a reason is refused.

Read the table

Column	Meaning
When	Date and time, for example **24 Oct 09:12**.
Actor	The admin who made the change, as the first eight characters of their account id. **system** for changes the platform made by itself. Hover for the full id.
Action	What happened, as a coloured pill, with the target next to it (a setting key, an invite code, an account id).
Reason	What the admin wrote. Select **before / after** to see the values before and after the change.

The actions you will see:

Action	Made by
`update_setting`, `clear_setting`	Saving or clearing a setting, including the budget, registration and model prices.
`suspend_user`, `unsuspend_user`, `erase_user`	The account actions on Users.
`create_invite`, `revoke_invite`	Invites.
`create_package`, `update_package`, `archive_package`	Packages.
`update_pricing`	Pricing.
`update_model_assignment`	The speech-to-text model.
`update_ai_route`	A job's model chain on Models.
`sync_ai_catalog`	**Sync models** on Models.
`run_safety_eval`	A safety test started on Models.

Secret settings (keys and passwords) are never written into the log. Their before and after only say whether a value was set, for example `{"configured": true}`.

Filter and export

- **Actor** and **Type** narrow the rows already loaded.
- **Load older** at the bottom loads the next 50 entries.
- **Export CSV** saves the log as a spreadsheet file, for the weekly review or for counsel.

Write reasons that will make sense later

Someone reading the log in six months should understand the change without asking you.

- Good: "Raised daily budget for beta wave 2: 8 more families from Monday."
- Not enough: "budget".
- Never: a family's email address, a child's name, or anything a child wrote.

ADMINS

The privacy boundary

Admins never see student messages, notes or images. This is how the console is built, not a setting.

TutorCat staff never see what children write or upload. Not their homework messages, not their wellbeing notes, not their photos or voice, not the tutor's replies. This is built into the server: an admin account has no access to student data at all. There is no switch to change it, and no screen in the console that could show it.

What admins can see

- **Counts and totals**: accounts, sessions, active students, consent rates, tokens, cost, safety events.
- **AI usage records**: for each AI call, which account it was for (shown by email and role only), the model, the job, the tokens and the cost. See below.
- **Account details**: email, role, plan, number of profiles, created date, suspended or active.
- **Feedback notes** that a family chose to send to the team, after being told the team reads them.
- **Payments**: the paying account's email, the package and the amount.
- **The audit log** of admin changes.

What admins cannot see

- A student's homework conversations, steps or answers.
- Photos of worksheets, voice recordings or transcripts.
- Session summaries, portfolio, wellbeing check-ins or notes.
- The content of any safety event. Safety events are shown as a count only.
- A feedback note's link to a session. There is none.
- The content of any AI call. Usage records hold no question, answer, photo or voice.

Parents see their own child's sessions in the parent area, except when a child tells us someone is hurting them, which stays private to keep them safe. Other serious concerns, such as self-harm, do alert parents.

AI usage records and OpenRouter

Costs shows what each account spent, so each usage record is linked to the student, or to the parent for a session summary. That link is metadata only: the account, the model, the job, tokens, cost and timing. **Message content is never in it.** The console shows the account's email and role, never a child's name. If a family is erased, the link is removed and the spending stays only as an anonymous total. See Costs.

Some AI jobs go through OpenRouter, a service that reaches many models with one key. Every request to it asks for zero data retention and no training on the data, and goes only to endpoints that promise both. A request is never sent without those protections. See Models.

What this means day to day

- **A bug report about a conversation.** Ask the parent for a screenshot from their parent dashboard. Reproduce it in a test account with the same grade and question.
- **A safety alert.** Never try to read the child's content or look up the individual event. Confirm from the counts that it was recorded. The child was shown helplines straight away, and linked parents were emailed (in some rare cases the child is shown support contacts only).
- **A parent calls about an alert.** Listen first. Do not ask for details of the child's messages. Point them to the helplines the child was shown.
- **Reasons and notes.** Never write a family's email, a child's name or anything a child wrote into an audit reason, a ticket or your recruiting sheet.



SAFETY

If you ever see a child's content, or another family's data, anywhere in the console, stop and report it at once. It is the highest-priority incident there is.

ADMINS

Daily beta operations

A checklist for every beta day, the weekly review, and what to do when something goes wrong.

The beta is small: 10 to 20 families, free, in the browser. A short routine every day catches almost everything. It takes about 15 minutes.

Every day

1. **Sign in** at tutorcat.ai/admin with your authenticator code.
2. **Overview → Launch readiness.** Expect **8 of 9 ready**, with only **Payments: Off** red.
   - **Tutor** says **Stub**, **Email** says **Logging only** or **Speech** says **Missing**: check the keys and SMTP in Settings, then tell engineering.
   - **Registration** must say **Invite only**.
   - **Dev flags** must say **None on**.
3. **Safety events (24h).** Write the number in your notes. Counts only: never try to read an event. If engineering tells you an alert email bounced, follow the runbook's safety alert steps.
4. **AI spend today.** Check it on Overview, and the bar on **AI & Usage**. If it is amber (80% or more) before the afternoon, find out why before tomorrow: a few heavy users, a loop, or a retry problem. Raise the budget only on purpose, with a clear reason.
5. **Feedback.** Read every new note. Reply to parents from beta@tutorcat.ai within one working day. Log bugs for engineering.
6. **Invites.** Check that new families signed up (their code's **Uses** went up, and **Accounts** on Overview moved). Send a short nudge to any family who has not signed up after 4 days. After 10 days, revoke their code and give the place to a new family.
7. **Parents waiting on consent.** If a child signed up first, make sure the parent has their own invite code. In invite-only mode they need one to create an account.
8. **Audit log.** Glance at yesterday's entries. Every change should be one you or a colleague expected, with a clear reason.
9. **Sign out** when you are done, or close the tab.

Every week

Pick a fixed time (for example Monday morning) and fill in one row of the beta metrics table. About 45 minutes.

1. **Feedback**: tag every note from the week (bug, confusing, request, praise); count bugs reported and fixed.
2. **Safety events**: the week's count from Overview. Ask engineering to confirm from the counts that the alert chain ran for every event.
3. **AI spend**: the week's cost and the cost per active family, from **AI & Usage → Usage and cost** (7d window). Download the CSV for the record if you like.
4. **Engagement**: active students and the funnel, from **Engagement** (7d window). In week 3, work out the share of families still active; the target is at least 70%.
5. **Backups and uptime**: confirm with engineering that every backup check was green.
6. **Audit log**: export the CSV and keep it with the week's notes.
7. **Decide**: what to fix, who to nudge. Write three lines of notes.

The safe settings, always

During the beta, **Settings** must stay at:

- `registration_mode = invite`
- `beta_all_access = true`
- `payments_enabled = false`
- `purge_enabled = false` (until counsel signs off)
- `voice_under_consent_age = false` (until counsel approves)

When something goes wrong

What happened	Do this in the console
Anything that could expose a child's data, or the site down for more than 30 minutes	It is a P0. Stop, tell engineering within the hour. To stop new sign-ups while it is fixed, make sure **Invite required** is on in Settings (and revoke codes not yet used if needed).
A code was forwarded or leaked	**Invites → Revoke**, then create a new code with the same label.
A family asks to pause an account	**Users → Suspend…** with the reason. Unsuspend later; nothing is lost.
A family emails asking for deletion	Point them to the delete option in the parent area first. If they need you to do it, **Users → Erase…** with the reason and the email retyped.
The tutor is paused for everyone	The daily budget is used up. Decide whether to wait for the next UTC day or raise it in **AI & Usage**, with a reason. Safety replies kept working throughout.
One child says the tutor told them to come back tomorrow	They reached the per-student allowance. That is working as intended. Raise **Per-student daily allowance (USD)** in Settings only if the default is clearly too low for normal homework.
A wrong tutor answer is reported	Ask the parent for a screenshot from their dashboard. Reproduce it in a test account. Never look for the child's conversation.

Going public

Going public happens once, after the beta's exit criteria are met and every go-public gate is checked, named and dated. The console part is short:

1. In **Settings**, turn off **Invite required** (sets `registration_mode` to `open`).

2. For a free launch, keep `beta_all_access = true` and `payments_enabled = false`. For a paid launch, set `beta_all_access = false` and `payments_enabled = true`.
3. Watch the first day: sign-ups, errors, AI spend, safety event counts and the feedback inbox. If something breaks, turn **Invite required** back on.

ADMINS

Admin FAQ

Quick answers to the questions staff ask most during the beta.

Can I read a child's conversation to understand a bug?

No. No admin can, by design: the console has no screen for it and the server refuses it. Ask the parent for a screenshot from their parent dashboard and reproduce the problem in a test account.

Why was I signed out in the middle of something?

Admin sessions last 30 minutes from sign-in and cannot be extended. The banner at the bottom warns you for the last five minutes. Sign in again with a fresh authenticator code.

My code was refused, but I typed it correctly.

Each code works only once. If you used it a moment ago, or tried twice, wait for the next one. The code from the previous 30 seconds still works, but older ones do not. If it keeps failing, set your phone's clock to automatic time.

I lost my phone. How do I get back in?

Ask engineering to re-enrol your authenticator. You get a new one-time setup link, and the old authenticator stops working at once. There is no reset by email.

Can I create another admin from the console?

No. Admin accounts are only created by engineering, never from the console or by signing up.

A parent says the sign-up page wants a code, but they came from a consent email.

In invite-only mode every new account needs a code, including a parent who arrived from their child's consent email. Create a code labelled with the family name (for example **Rahman parent**) and send it to them.

How many uses should a code have?

One code covers a family: the parent and each child use it once. The default of 5 fits one parent and up to four children. For a second parent with their own code, create a separate one labelled, for example, **Rahman 2**.

I revoked a code by mistake. Can I undo it?

No. Create a new code with the same label and send it to the family. Accounts already made with the old code keep working.

What does a suspended family see, and is anything deleted?

A suspended account cannot sign in. Nothing is deleted. Unsuspend it and everything is still there.

Why does Payments look red and say no provider is connected?

Because payments are off for the beta, which is correct. The panel shows whenever **Payments open** is off. Do not change it during the beta.

Why does the Plan column show "—" for everyone?

Nobody has a paid subscription in the beta. Families get Family features through **Everyone gets Family features** (`beta_all_access`), not through a plan.

The tutor stopped for everyone. Is it broken?

Probably not. Check **AI spend today** on Overview: if it is red, today's budget is used up and the tutor is paused. Safety replies kept working. It restarts when the UTC day turns, or within a minute of raising the budget in **AI & Usage**.

Do we get warned before the budget runs out?

There is no automatic warning before 100%. The budget bar turns amber at 80%; check it every day. At 100% one email goes to the support address.

How do I see what a setting is set to?

You cannot see the value; the console is write-only. The row shows whether it is set, when and by whom. For non-secret settings, the **Audit log**'s **before / after** shows the value at each change.

When can we turn on purge_enabled?

Only after counsel has signed off on the retention periods. Until then it stays off, and no child's account is erased automatically.

Can someone change or delete an audit entry?

No. The log is append-only, and the database refuses edits and deletions.

Can I use the console on my phone?

Yes. Tap **Open menu** at the top right to move between sections. Reading feedback and copying invite codes work well on a phone. Make larger changes, such as settings, on a computer.

A model I picked was refused. Why?

The picker shows the reason beside the model, for example **No image input**, **No streaming**, **No zero-retention endpoint** or **Needs a safety test**. Each job needs certain abilities, and an OpenRouter model must have a zero-data-retention endpoint. Pick another model, or for the safety screen run the test first. See Models.

Natural voices are on, but a child still hears the device voice. Why?

The device voice takes over whenever the natural voice cannot read: the OpenRouter key is not set, every voice model in the **Narration voices** chain failed, or the daily budget or that child's allowance is used up. After a budget or allowance stop, the app tries the natural voice again five minutes later. Check the key and the chain on Models, and spend on AI and usage.

A whiteboard picture is wrong. How do I remove it?

Open **Models**, find it in **Diagram library**, select **Delete** and give a reason. It is never shown again. Boards that showed it draw their labels instead, and the next board that needs it gets a new picture that is checked again. See The diagram library.

Can children's data ever go to a model without zero data retention?

No. Every OpenRouter request asks for zero data retention and no training on the data, and goes only to endpoints that promise both. If none can serve the model, the request moves on to the next model in the chain instead. It is never sent without those protections.

Will a child notice when a model fails and a backup takes over?

No. The next model in the chain answers, and nothing changes on the child's screen. If every model fails, the child sees the usual friendly "try again" message, never placeholder text. The **Failovers** log on Models shows how often it happened.

Why did the safety screen stop using a model?

Its safety test expired. A pass counts for 90 days, then the model is no longer allowed on the safety screen until it is tested again. The keyword check kept running throughout. Run the test again from **Edit** on **Safety screen**.

Why is the cost on Costs different from what OpenRouter charged?

Some calls are only estimated: tokens multiplied by the price table. **Where the figures come from** shows the split between provider-reported and **Estimated** spend. A model marked **Not priced** counts at $0, which makes the total too low. Fix the price on **AI & Usage**.

Can I see what a child asked, or their name, on Costs?

No. Costs shows an email and a role per account, with tokens and cost. It never shows a child's name and holds no message content. If a family is erased, their spending stays in the totals but is no longer linked to anyone.

How do I find the student who is using the most?

Open **Costs**, go to **By account** and sort by **Cost**. Select an account to see its days, jobs and models. For a parent, the **Family** column adds their children's cost.